

## TYPAR® METROWRAP For Commercial Applications:

### TYPICAL CHARACTERISTICS:

Thickness		12.1 m
Base Weight	Tappi T-410	3.5 oz/yd <sup>2</sup>
Breaking Strength (grab tensile)	(ASTM D-5034) (ASTM D-5034)	93 lbs MD 95 lbs CD
Trapezoidal Tear Resistance	(ASTM D-1117)	60 lbs MD 67 lbs CD
Water Resistance Test	ATTC-127	980 cm
Air Penetration Resistance	Tappi T-410	>4800 sec/100cc
Water Vapor Transmission	ASTN E 96 Method A	10 Perms
Ultra Violet Light Exposure Resistance (UV)		12 months
Surface Burning Characteristics Flame Spread Index Smoke Developed Index	ASTM E84	Class A PASS

**Roll sizes:** 10 ft x 100 ft, 5 ft x 150 ft

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, we make no warranty, expressed or implied, of merchantability, fitness or otherwise, or of the results to be obtained, or against patent infringement, and we disclaim all liability from any resulting damage or loss.

TYPAR®, TYPAR® Weather Protection System, and TYPAR® MetroWrap, are registered trademarks of Polymer Global, Inc.